

Specification


Code:460-8660

Nominal Voltage	12V
Watts(15min Rate)	675.8 Watte at 1.67V/cell
Dimension	Length 522±3mm (20.55 inches)
	Width 240±3mm (9.45 inches)
	Container Height 218±3mm (8.58 inches)
	Total Height (with Terminal) 224±3mm (8.81 inches)
Approx Weight	Approx 62.2 kg (137.1lbs)
Terminal	T11
Container Material	ABS
Rated Capacity	206.0 AH/20.6A (10hr , 1.80V/cell,25°C/77°F)
	200.0 AH/25.0A (8hr, 1.80V/cell,25°C/77°F)
	174.5 AH/34.9A (5hr, 1.75V/cell,25°C/77°F)
	158.4 AH/52.8A (3hr, 1.75V/cell,25°C/77°F)
	136.0 AH/136.0A (1hr, 1.60V/cell,25°C/77°F)
Max. Discharge Current	2000A (5s)
Internal Resistance	Approx 2.7mΩ
Operating Temp.Range	Discharge : -15~50°C (5~122°F)
	Charge : 0~40°C (32~104°F)
	Storage : -15~40°C (5~104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)
Cycle Use	Initial Charging Current less than60.0A.Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C
Capacity affected by Temperature	40°C (104°F) 103%
	25°C (77°F) 100%
	0°C (32°F) 86%
Self Discharge	Leoch LPX series batteries may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.



Applications

- ◆ UPS (High rate)
- ◆ High power backup supply
- ◆ Emergency power supply
- ◆ Starting system
- ◆ Power tools
- ◆ Emergency lighting
- ◆ Electric starting



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	321.6	277.6	237.0	181.6	138.1	113.8	66.7	48.7	38.5	32.2	28.6	23.9	20.0	10.3
1.80V/cell	351.6	296.8	246.6	190.8	143.2	120.8	71.1	51.7	40.6	34.0	30.1	25.0	20.6	10.7
1.75V/cell	375.6	314.1	262.8	198.4	148.3	124.0	72.9	52.8	41.8	34.9	30.7	25.3	20.9	10.8
1.70V/cell	409.2	335.4	274.8	204.8	153.3	128.0	74.2	54.1	42.7	35.5	31.3	25.5	21.2	10.9
1.67V/cell	439.2	359.5	288.0	210.4	156.3	132.0	75.7	54.7	43.5	36.1	31.7	25.8	21.4	11.0
1.60V/cell	459.6	374.3	296.4	216.0	160.3	136.0	77.0	55.9	44.3	36.6	32.1	26.0	21.5	11.1

Constant Power Discharge (Watts/cell) at 25 °C (77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	609.4	536.6	461.7	356.1	272.6	225.7	132.7	97.2	77.1	64.7	57.6	48.3	40.5	20.9
1.80V/cell	661.4	570.2	477.7	372.4	281.1	238.5	141.1	102.9	81.0	68.2	60.5	50.4	41.6	21.6
1.75V/cell	701.2	599.7	506.7	385.7	290.2	244.2	144.2	104.8	83.2	69.6	61.5	50.8	41.9	21.7
1.70V/cell	757.8	636.2	527.1	396.5	299.2	251.3	146.3	107.0	84.8	70.7	62.4	51.0	42.4	21.8
1.67V/cell	805.5	675.8	548.4	405.0	303.5	258.1	148.8	108.0	86.1	71.8	63.2	51.4	42.7	22.0
1.60V/cell	834.2	697.8	559.6	412.6	309.3	264.7	150.7	109.8	87.4	72.5	63.8	51.8	43.0	22.1



Specifications subject to change without notice.




Dimensions

T11 Terminal


Unit: mm [inches]




Discharge Characteristics





Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Effect of Temperature on Long Term Float Life



Self Discharge Characteristics

- A** No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
 2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
 3. Charged for 8-10 hours at limited current 0.05CA.
- C** Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

Sales Office

Finland and Baltic countries

Celltech Oy
Höyläämötie 11 A, 00380 Helsinki, Finland
TEL: +358 (0) 207 999 640
E-mail: info@celltech.fi
www.celltech.fi

Denmark

Celltech A/S
Lejrvej 25, 3500 Væroløse, Denmark
TEL: +45 7025 2201
E-mail: info@celltech.dk
www.celltech.dk

Norway

Staubo Elektro-Maskin AS
Bjoernerudveien 12 C, 1266 Oslo, Norway
TEL: +47 22 75 35 00
E-Mail: post@staubo.no
www.staubo.no